

# **YC-725L**





#### Real Air Cooling

The multi-duct vortex refrigeration system and finned evaporator can prevent frosting completely and improve temperature uniformity to a large extent.

### Real Energy Saving

The refrigerator is equipped with "M + Energy Core" power management system and complete air cooling design, improving energy saving efficiency by more than 40%.

The electrical heating + LOW-E design with double considerations can achieve a better anti-condensation effect for the glass door.

#### Real Safety

Seven temperature probes can ensure high precision of temperature control with nearly no fluctuation and thus can improve safety.





#### Intelligent Temperature Control

- Equipped with high-precision microcomputer temperature control system and 1 high-brightness digital temperature display with display accuracy at 0.1°C.
- · Equipped with a remote alarm access port and 485 data access port.



#### **Security System**

·The well-developed audible & visual alarm system with multiple audible & visual alarm functions: high temperature alarm, low temperature alarm, sensor failure alarm, door ajar alarm, power outage alarm etc;

- The turn-on delay and stopping interval protection function can ensure reliability in running;
- ·The door is equipped with a lock, preventing it from opening accidentally.



#### **Refrigeration System**

Equipped with a compressor supplied by an international famous brand, high-efficiency air-cooled condenser and finned evaporator, ensuring fast refrigeration.



- · Equipped with a USB export interface, which can be used for exporting data in PDF;
- · When a U-disk is connected, temperature data can be stored continuously and automatically (data can be stored for 100,000 sets of data);
- ·The printer is optional.



#### **Human-oriented**


- Equipped with high-quality shelves made from PVC-coated steel wire with tag cards and classification marks, which are easy to clean;
- $\cdot$  Equipped with an invisible door handle, ensuring elegance of appearance;
- Equipped with a testing port, bringing convenience to users in testing temperature inside the cabinet;
- Inside with lighting system for easy look. The light will turn on while door is opened, light will goes off while the door is closed.




## Scope of Application

Suitable for storage of biological products, vaccines, drugs, reagents, etc. Suitable for use in pharmacies, pharmaceutical factories, hospitals, centers for disease prevention & control, clinics, etc.

## Performance Data / Cooling Curve



## **External Dimensions**



2.0°C Pharmacy Pofrigorator	
2~8°C Pharmacy Refrigerator	V0 7051
Model	YC-725L
Cabinet Type	Upright
Capacity(L)	725
Internal Size(W*D*H)mm	980*595*1260
External Size(W*D*H)mm	1093*772*1992
Package Size(W*D*H)mm	1187*795*2136
NW/GW(Kgs)	171/208
Performance	
Temperature Range	2~8°C
Ambient Temperature	16-32°C
Cooling Performance	5℃
Climate Class	N
Controller	Microprocessor
Display	Digital display
Refrigeration	
Compressor	1pc
Cooling Method	Air cooling
Defrost Mode	Automatic
Refrigerant	R290
Insulation Thickness(mm)	55
Construction	
External Material	PCM
Inner Material	Aluminum plate with spraying/Stainless steel (optional)
Shelves	12(coated steel wired shelf)
Door Lock with Key	Yes
Lighting	LED
Access Port	1pc. Ø 25 mm
Casters	4+ (2 casters with brake)
Data Logging/Interval/Recording Time	USB/Record every 10 minutes / 2 years
Door with heater	Yes
Alarm	
Temperature	High/Low temperature,High ambient temperature,Condenser overheating
Electrical	Power failure , Low battery
System	Sensor failure, Door ajar, Built-in USB datalogger failure, Communication failure
Electrical	
Power Supply(V/HZ)	220-240~/50
Rated Power(W)	540
Power Consumption(KWh/24h)	8.42
Rated Current(A)	3.90
	3.90
Rated Current(A)  Accessories Standard	3.90  RS485, Remote alarm contact, Backup battery

 $<sup>{}^{\</sup>star}\text{The model, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading.}$ 

<sup>\*</sup>There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.



Fax: 495 220 154