

Varioshake VS 8 B - reciprocating shakers

Order code: **1304.L003058**



Information about product price on demand

Parameters

Device type

Manufacturer

Maximum speed

Dimension of moving base

Max. amplitude

Rotational Speed

Shaking motion

Maximum load

Quantitative unit

Shaker

LAUDA

300 rpm

330 × 330 mm

20 mm

20 - 300 rpm

Reciprocal

8 kg

ks

Specifications and features

- Robust, space-saving and quiet reciprocating shaker
- Excellently applicable for continuous operation
- Electronic speed control, stepless, with gentle start-up
- Clearly laid out control panel for easy operation
- An a.c. motor with overload protection drives the unit
- Compact, low-wear counterbalanced drive mechanism
- Constant speed independent of load
- Shaking platform made of anodised aluminium
- Housing made of high impact strength polystyrene
- Comprehensive range of accessories

Applications

This shaker is successfully used in medical diagnostics or analysis as well as for growing micro-organisms, cell and tissue cultures. It is particularly used in laboratories, incubation and moderating rooms at ambient temperatures between +10 and +50 °C.

Optional Accessories:

3950, 3951, 3952, 3953, 3956, 3957, 3958, 3959, 3983, 3984, 3985, 3986, 3987, 3988