



HELAGO-CZ, s.r.o.  
Commercial Register maintained by the Regional Court in  
Hradec Králové  
Section C, File 17879  
Kladská 1082  
500 03 Hradec Králové 3  
Company ID: 25 96 39 61, VAT: CZ 25963961  
Phone: 495 220 229, 495 220 394  
Fax: 495 220 154  
GSM gate: 602 123 096  
E-mail: [info@helago-cz.cz](mailto:info@helago-cz.cz)  
Web: <http://www.helago-cz.cz>

## **VBFT.196.60.4-G - Safety Cabinet type 90**

Order code: **8101.VBFT196604G**



Information about product price on demand

### Parameters

Types of safety cabinets

Typ 90 - skládací dveře

Quantitative unit

ks

- Safe and approved storage of hazardous materials in workrooms
- 90 min. fire resistant cabinet in accordance with EN 14470-1 (Type 90)
- Door open arrest system (standard)

- Cylinder locking (suitable for masterkey systems)
- Extraction air inlet on the top
- Adjusting aids to compensate for uneven floor
- Earthing link (standard)

### **Manual Operating**

- Smooth, air-damped door closing
- Minimal effort: one-hand door operation easy and safe
- Door closing system outside the storage compartment: increased protection of moving and safety relevant components against corrosion

### **Folding Doors**

- Less depth while open, space saving
- 90° opening, interior of the cabinet completely visible
- Protection by vertical anti-trapping door strip

### **Your safety in the event of fire**

- Automatic closing of the door by an integrated thermal release system (fusible link)

### **Drawers**

- High storage capacity
- Sealed by welding, impervious to fluids
- Fully extractable, smooth running, with permanent delayed self-closing
- Load capacity per drawer: approx. 60 kg

### **Cabinet with width of 600 mm (VBFT196.60)**

- Folding door
- Dimensions W × D × H (mm): exterior approx. 600 × 615 × 1968, interior approx. 450 × 520 × 1 740
- Weight approx. 260 kg
- Bottom collecting sump volume 22 l