

HELAGO-CZ, s.r.o. Commercial Register maintained by the Regional Court in Hradec Králové Section C, File 17879 Kladská 1082 500 03 Hradec Králové 3

Company ID: 25 96 39 61, VAT: CZ 25963961 Phone: 495 220 229, 495 220 394

Fax: 495 220 154 GSM gate: 602 123 096 E-mail: info@helago-cz.cz Web: http://www.helago-cz.cz





Cena bez DPH 168,40 Eur
Price with VAT 203,76 Eur

Parameters

Device type Pen-type pH meter Measuring range $0,0 \dots 14,0$ pH Measuring accuracy $\pm 0,02$ pH Description Pro kapalná média

Temperature display YES
Quantitative unit ks

The testo 206 pH1 features a new kind of probe technology that almost totally avoids broken glass. The probe design incorporates a large volume of the gel-reference electrode, which guarantees a long service life. Other innovations in the probe design, including the whole diaphragm, ensure that the probe is not affected by dirt and is easy to clean within seconds.

The instrument has been designed with ease of use in mind. The pH-probes can be easily and quickly calibrated to one, two or three points (pH-values 4/7/10) and measured values are easy to read thanks to the illuminated display.

All functions can be switched on or off by the user himself.

The testo 206 pH1 also offers users the combination of pH-penetration tip and temperature probe. Temperature compensation and recognition of the final value are done automatically.

The testo 206 pH1 is available in a practical set including protection case "TopSafe", belt clip and storage cap. The ph meter is suitable for use with liquid media in all sectors including:

- pH-determination in the environment (water, waste water)
 condensate neutralisation (heating technique / condensing boiler)
- pH-applications in the industrial sector (lubricants)
- pH-measurement in the food sector (production of fruit juices)