

DC Power Supply 0-500 V (230 V, 50/60 Hz)

Order code: **5401.1003308**



Cena bez DPH

850,00 Eur

Price with VAT

1.028,50 Eur

Parameters

Quantitative unit

ks

Low voltage power supply with four outputs primarily intended to simultaneously supply power for the Teltron line of electron tubes and Helmholtz Coils, with four independent, adjustable DC voltages. The DC voltages are stabilized, regulated, floating, and galvanically isolated from one another, in addition to being short circuit proof and secure from external voltages.

Specifications:

500 V output:

- Voltage: 0 – 500 V DC, max. 50 mA
- Stability at full load: $\leq 0.01\% \pm 100 \text{ mV}$
- Residual ripple: $\leq 20 \text{ mV}$

50 V output:

- Voltage: 0 – 50 V DC, max. 50 mA

- Stability at full load: $\leq 0.1\% \pm 30 \text{ mV}$
- Residual ripple: $\leq 50 \text{ mV}$

12 V output:

- Voltage: 0 – -12 V DC, max. 4 A
- Stability at full load: $\leq 0.1\% \pm 30 \text{ mV}$

8 V output:

- Voltage: 0 – 8 V DC, max. 3 A
- Stability at full load: $\leq 0.1\% \pm 30 \text{ mV}$

Displays: Analogue, class 2

Connections: 4 mm safety sockets

Power consumption: 50 VA