


HELAGO-CZ, s.r.o. Commercial Register maintained by the Regional Court in Hradec Králové Section C, File 17879 Kladská 1082 500 03 Hradec Králové 3 Company ID: 25 96 39 61, VAT: CZ 25963961

Fax: 495 220 154 GSM gate: 602 123 096 E-mail: info@helago-cz.cz Web: http://www.helago-cz.cz

Phone: 495 220 229, 495 220 394

VBFT.SL+P4Z - Width 1 200 mm, combinated doors





Information about product price on demand

Parameters

Types of safety cabinets Typ 90 - kombinované dveře

Color Světle šedá

Interior equipment 4 police + 4 výsuvné police

Quantitative unit

• Combi-Cabinet for flammable liquids, acid and alkalis

- Safe and approved storage of hazardous materials in workrooms
- 90 minutes fire resistance cabinet in accordance with EN 14470-1
- Cylinder locking (suitable for masterkey systems)
- The extraction air inlet is flush with the ceiling of the cabinet
- Adjusting aids to compensate for uneven floor
- Earthing link (standard)

Operation

- Smooth, air-damped door closing
- Minimal effort: door opening easy and safe
- Door closing system outside the storage compartment: increased protection of moving and safety relevant components against corrosion

ks

Doors

- 90° opening, interior of the cabinet completely visible
- Less depth open, space saving, protection by vertical anti-trapping door strip

Door open arrest system (standard)

- Holds door open and eases the storage and removal inside the cabinet
- Door open arrest system with an ingrated, thermal release system (fusible link), automatic closing of the doors

Interior equipment

Drawers (for flammable liquids)

- High storage capacity (see table), fully extractable, smooth running
- Sealed by welding, impervious to fluids
- Load capacity per drawer (evenly distributed load): approx. 25 kg

Shelves (for flammable liquids)

- 3 adjustable shelves with inclination and pull-out protection, adjustable in different height in 32 mm load on one shelf (uniform distributed) approx. 75 kg
- 1 perforated metal plate incerted at the bottom of collecting sump
- Easily removable bottom collection sump with three-sided lip seal for safe collection of leakage

Pull-out shelves (for acid and alkalis)

- Load capacity per drawer (evenly distributed load): approx. 25 kg
- Capacity: approx. 15 litres

Cabinet with width of 1 200 mm

- One wing door and one folding door
- Dimensions W \times D \times H (mm): exterior approx. 1 200 \times 615 \times 1 968 mm, interior approx. 1 050 \times 520 \times 1 740 mm
- Weight: approx. 420 kg