

## **AD-8127 - Multi-functional compact printer for balances/scales**

Order code: **0107.AD8127**



Cena bez DPH

1.000,00 Eur

Price with VAT

1.210,00 Eur

Parameters

Type Balances

Approval (Verif. ČMI)

Quantitative unit

Accessories

NO

ks

### **Features**

- Easy setting and operation with a numeric keypad and LCD display
- Built-in calendar and clock for printing date and time at any time
- Sends re-zero and weighing data request commands to the balance/scale

- Clear and visible dot matrix printing, which also enables long-term preservation of the printed records
- Compact and lightweight for portability and installation anywhere
- Interval printing mode for printing weighing data at set intervals
- Chart printing mode for printing time-series variations of weighing data
- Dump printing mode to receive and print GLP/GMP/GCP/ISO compliant output from the balance/scale
- Performs and prints the results of statistical calculation including standard deviation
- Prints an ID number set for the printer at any time
- Dust-free paper (AX-PP173-S) available for use in clean rooms
- Two types of RS-232C cables (D-Sub 25P and D-Sub 9P) provided as standard to connect to balances/scales with different interfaces\*
- Comes with an AC adapter as standard
- Receives a print, paper feed, print statistical calculation results, print total, re-zero, or weighing data request command from the optional foot switch (AX-SW128)

\* The cables can be changed to either a DIN or current loop cable at time of order.

### Accessories

- AX-PP137-S : Plain printer paper (10 rolls)
- AX-PP173-S : Dust-free printer paper (10 rolls)
- AX-ERC-22B-S : Ink ribbon (5 pcs)

### Specifications

Character specifications: 7 × 9 dots, 1.6 (W) × 3.2 (H) mm

Printing speed: Approx. 1.6 lines/second

Paper feeding speed: Approx. 4 lines/second

Number of characters printed: 24 characters/line

Printer paper width: 57.5 mm

Operating environment: 0 to 40 °C/32 to 104 °F, 35 to 85%RH (no condensation)

Storage environment: -20 to 60 °C/-4 to 140 °F, 10 to 90%RH (no condensation)

Interface: RS-232C (D-Sub 9P, male) / Current loop (DIN)

Power supply: AC adapter

Size / weight: 174 (W) × 141 (D) × 87 (H) mm / approx. 500 g

Standard accessories: Ink ribbon (1 pc), plain printer paper (1 roll), AC adapter, AC adapter label, instruction manual, two RS-232C cables (D-Sub 25P and D-Sub 9P)\*

\* The cables can be changed to either a DIN or current loop cable at time of order.