



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in
Hradec Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: <http://www.helago-cz.cz>

BIO100CYTO - Biological Safety Cabinet
class 2 - BIO100 CYTO
Order code: **1503.BIO100CYTO**



| | |
|----------------|--------------|
| Cena bez DPH | 7.710,00 Eur |
| Price with VAT | 9.329,10 Eur |

Parameters

| | |
|-----------------------------------|--------------------------------------------------|
| Inner dimensions (w x d x h) [mm] | 950 x 645 x 660 mm |
| Description | Biological Safety Cabinet class II width 1000 mm |
| Ext. dimensions (wxdxh) | 1040 x 790 x 2069 mm |
| Price info | Price does not include shipping and validation |
| Quantitative unit | pcs |

Biological Safety Cabinet class II width 1000 mm (BIO100 CYTO - A2) adapted for operation with cytostatics.

Specification of the biological safety cabinet class 2 - BIO100 CYTO

- vertical laminar air flow
- 3 HEPA filters with efficiency of 99.995% for MPPS
- exhaust carbon filter in compliance with DIN 12980
- microprocessor control system with touchscreen in Polish/English or any other language
- automatic filter compensation ensures constant and safe speed of air flow in the cabinet
- hour timer of the cabinet and UV lamp operation
- adjusted air flow
- clear and easy-to-use control panel - optical and acoustic signals
- silent fans, noise level below 56 dB
- front window made of tempered double glass without frame, inclined at an angle of 8°, electrically raised and lowered, with a possibility to shut it completely - closing the workspace
- split worktop (3 autoclavable boards), made of stainless steel
- internal workspace made of stainless steel
- permanently fixed UV lamp in the upper part of the workspace, protected from accidental switching on during operation
- white fluorescent lightning system min. 1200 lux
- workspace sides with window openings
- two power sockets inside workspace
- removable armrest
- frame with lockable castors
- power supply 230V/60 Hz

Standard equipment of the biological safety cabinet class 2 CYTO

- additional lamp above the workspace
- UV germicidal lamp
- power sockets inside the workspace
- basis under the laminar-flow cabinet