

HELAGO-CZ, s.r.o. Commercial Register maintained by the Regional Court in Hradec Králové Section C, File 17879 Kladská 1082 500 03 Hradec Králové 3 Company ID: 25 96 39 61, VAT: CZ 25963961

Phone: 495 220 229, 495 220 394

Fax: 495 220 154 GSM gate: 602 123 096 E-mail: info@helago-cz.cz Web: http://www.helago-cz.cz BIO130 - Biological Safety Cabinet class 2 - BIO130

Order code: **1503.BIO130**



Cena bez DPH
Price with VAT

6.980,00 Eur

8.445,80 Eur

Parameters

Inner dimensions (w \times d \times h) [mm] 1250 \times 645 \times 660 mm

Description Biological Safety Cabinet class II

Ext. dimensions ($w \times d \times h$) 1340 \times 790 \times 2069 mm

Price info Price does not include shipping and validation

Quantitative unit p

Biological Safety Cabinet class II width 1300 mm with adjusted air flow (BIO130 - A2)

Specification of the biological safety cabinet class 2 - BIO130

- vertical laminar air flow
- II safety class
- 2 HEPA filters with efficiency of 99.995% for MPPS
- microprocessor control system with touchscreen in Polish/English or any other language
- automatic filter compensation ensures constant and safe speed of air flow in the cabinet
- hour timer of the cabinet and UV lamp operation
- · adjusted air flow
- clear and easy-to-use control panel optical and acoustic signals
- silent-running fans
- front window made of tempered double glass without frame, inclined at an angle of 8°, electrically raised and lowered, with a possibility to shut it completely closing the workspace
- split worktop, made of stainless steel
- internal workspace made of stainless steel
- permanently fixed UV lamp in the upper part of the workspace, protected from accidental switching on during operation
- white fluorescent lightning
- workspace sides with window openings
- removable armrest
- frame with lockable castors
- power supply 230V/60 Hz
- digital time counter of cabinet and inner oversee system of errors.

Standard equipment of the biological safety cabinet class 2

- additional lamp above the workspace
- UV germicidal lamp
- 2 power sockets inside the workspace
- basis under the laminar-flow cabinet