

BIO160 - Biological Safety Cabinet
class 2 - BIO160
Order code: **1503.BIO160**



Cena bez DPH

9.160,00 Eur

Price with VAT

11.083,60 Eur

Parameters

Inner dimensions (w x d x h) [mm]

1561 x 645 x 660 mm

Description

Biological Safety Cabinet class II

Ext. dimensions (wxdxh)

1640 x 790 x 2069 mm

Price info

Price does not include shipping and validation

Quantitative unit

pcs

Biological Safety Cabinet class II width 1600 mm (BIO160 - A2)

Specification of the biological safety cabinet class 2 - BIO160

- vertical laminar air flow
- II safety class
- 2 HEPA filters with efficiency of 99.995% for MPPS
- microprocessor control system with touchscreen in Polish/English or any other language
- automatic filter compensation ensures constant and safe speed of air flow in the cabinet
- hour timer of the cabinet and UV lamp operation
- adjusted air flow
- clear and easy-to-use control panel – optical and acoustic signals
- silent-running fans
- front window made of tempered double glass without frame, inclined at an angle of 8°, electrically raised and lowered, with a possibility to shut it completely – closing the workspace
- split worktop, made of stainless steel
- internal workspace made of stainless steel
- permanently fixed UV lamp in the upper part of the workspace, protected from accidental switching on during operation
- white fluorescent lightning
- workspace sides with window openings
- removable armrest
- frame with lockable castors
- power supply 230V/60 Hz
- digital time counter of cabinet and inner oversee system of errors

Standard equipment of the biological safety cabinet class 2

- additional lamp above the workspace
- UV germicidal lamp
- 2 power sockets inside the workspace
- basis under the laminar-flow cabinet