

HELAGO-CZ, s.r.o. Commercial Register maintained by the Regional Court in Hradec Králové Section C, File 17879 Kladská 1082 500 03 Hradec Králové 3 Company ID: 25 96 39 61, VAT: CZ 25963961

Fax: 495 220 154 GSM gate: 602 123 096 E-mail: info@helago-cz.cz Web: http://www.helago-cz.cz

Phone: 495 220 229, 495 220 394

411011 - Diaphragm pump MP 065 E

Order code: **8010.411011**



Cena bez DPH 545,00 Eur
Price with VAT 659,45 Eur

Parameters

Pumping rate [l/min] 11,6

Treshold pressure [kPa] <10

Vacuum pump Diaphragm

Quantitative unit ks

This standard duty diaphragm pump model is a high performance and easy-to-use solution for small benchtop desiccators as it has a small footprint. With a total weight of 2.3 kg it is also portable. Further this model also provides a low sound level during operation with below 45 dB(A).

Technical Data

• Number of heads / stages: 2/1

• Max. pumping speed at 50 Hz in m³/h (I/min): 0.7 (11.6)

• Ultimate pressure in mbar (Torr): < 100

• Wired for: 90 to 260V AC

• Intake connection: Hose nozzle DN 6

• Exhaust connection: Hose nozzle DN 6 with removable exhaust silencer

• Sound level (dB): < 45

• Dimensions (W/D/H) in mm: 144/127/196

• Motor voltage: 18 VDC

• Operating temperature in °C: 10 - 60 °C

• Weight kg (lbs): 2.3 (5.1)