

U2522C-02 - Piston pump WOB-L® 2522

Order code: **8010.U2522C-02**



Cena bez DPH

564,00 Eur

Price with VAT

682,44 Eur

Parameters

Pumping rate [l/min]

18,3

Threshold pressure [kPa]

13,3

Vacuum pump

Piston

Quantitative unit

ks

WOB-L® 2522 dry piston pumps are a reliable partners for physical applications, notably with aqueous solutions. Being a vacuum pump and compressor, they can be used for a wide variety of applications such as filtration, gas sampling, vacuum drying, desiccation and automation technology. The integrated vacuum and pressure gauges and regulators allow the pressure to be continuously monitored and adjusted. The pump is protected by an inlet liquid trap with automatic flow stop.

For use with dry or aqueous vapor applications only.

Advantages:

- oil free
- easy to clean
- easy maintenance
- easy handling and control features
- robust construction

Technical Data

- Max. pumping speed at 50 Hz in m³/h (l/min): 1.1 (18.3)
- Max pumping speed at 60 Hz in m³/h (l/min): 0.76 (22)
- Max. pumping speed at 60 Hz in cfm (l/min): 0.76 (22)
- Ultimate pressure in mbar (Torr): 133
- Wired for: 230V, 50Hz
- Dimensions (W/D/H) in mm: 206/224/254
- Weight kg (lbs): 5.3 (11.7)