



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in Hradec
Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: <http://www.helago-cz.cz>

**B-292LD1 - Laboratory binocular
microscope**

Order code: **0501.B292LD1**



Cena bez DPH

2.213,00 Eur

Price with VAT

2.677,73 Eur

Parameters

Microscopes types

Laboratory

Serie

B-290

Number of eyepieces

Binocular

Number of lenses	4
Zoom of lenses	10×, 20×, 40×, 100×
Illumination	X-LED
Quantitative unit	ks

- Observation mode:
- Brightfield.
- Head:
- Binocular, 360° rotating and 30° inclined.
- Interpupillary distance 48-75mm.
- Dioptic adjustment:
- On the left eyepiece tube.
- Eyepieces:
- WF10x/20 mm, high eye-point and secured by a screw.
- Nosepiece:
- Quadruple revolving nosepiece, rotation on ball bearings.
- Objectives:
- Equipped with binocular head and following objectives:
- IOS N-PLAN 10x/0.25 (Cover/No Cover), with anti-fungus treatment
- IOS N-PLAN 20x/0.40 (Cover/No Cover), with anti-fungus treatment
- IOS N-PLAN 40x/0.65 (Cover/No Cover), with anti-fungus treatment
- IOS W-PLAN 100x/0.80 (No Cover, Dry), with anti-fungus treatment
- Specimen stage:
- Double layer rackless mechanical sliding stage, 150×139 mm, 75×33 mm X-Y movement range. Vernier scale on the two axes, accuracy: 0.1 mm.
- Focusing:
- Coaxial coarse and fine focusing mechanism with limit stop to prevent the contact between objective and specimen. Adjustable tension of coarse focusing knob.
- Condenser:
- Abbe N.A. 1.25, with objective-coded iris diaphragm, focusable and centerable.
- Brightfield Illumination (Fixed Koehler type):
- X-LED3 with white 3.6 W LED (6,300 K) and light intensity control.
- Multi-plug 100-240Vac/6Vdc external power supply.
- Fluorescence Illumination:
- Extra efficiency LED, with light intensity control. Peak wavelength: 465 nm, Power: 3.6W.
- Epi Fluorescence Attachment:
- Slider with 3 positions (2 fluorescence, 1 brightfield), with 1 included filterset: Fluorescence B: EX 460-490, DM 505, EM 515LP: Acridine Yellow, Acridine Orange, Auramine, DiO, DTAF,
- FITC, GFP, YFP, etc.