

TM-17SG - Hotplate Stirrer

Order code: **9002.AAH34275K**



Cena bez DPH

650,00 Eur

Price with VAT

786,50 Eur

Parameters

Device type	Magnetic stirrers
Types of stirrers	Magnetic
For volume [l]	20
Speed [rpm]	2000
For volumes upto [l]	20
Max. volume [l]	20
Plate diameter [mm]	170
Heating capacity [W]	800
Heating	YES
Maximum speed	2000 rpm
Number of positions	1
Quantitative unit	ks

Performance & Convenience

- Integrated design of the heater and the top plate provides exceptional heat transfer rate and quick heat up capability.
- Fast and precise stirring operations are enabled by BLDC motor and special magnet with extremely strong magnetic coupling power.
- Instant halt of the stirring operation due to the exceptionally fast response characteristics.
- Smooth-start mechanism provides virtually no decoupling of stir bars even with viscous media.
- Large stirring capacity up to 20 liter in case of water.
- Non-slip heating bath with concavo-convex bottom prevents unintentional slips of the bath. (optional)
- A transparent safety shield protects users from liquid splashes. (optional)
- Support rod allows for diverse flexibility in configuring other test equipment and accessories. (optional)

Safety

- Built in thermal shutdown and current limit protection.
- Hot top warning Indicator for preventing accidental injuries.
- ※ CSA except for TM-18QG. ※ RoHS for TM-14SG.