



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in
Hradec Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: <http://www.helago-cz.cz>

Centrifuge 5430 with Rotor
FA-45-30-11 incl. rotor lid
Order code: **1309.5427000210**



Cena bez DPH
Price with VAT

4.170,00 Eur
5.045,70 Eur

Parameters

Device type	Centrifuges
Test tube volume [ml]	1,5/2,0
Max. speed	17500 rpm
Quantitative unit	ks

Unique cross-over Centrifuge 5430 and 5430 R combine the best features of a microcentrifuge (small footprint) and multipurpose centrifuge (versatility) in one instrument. These centrifuges spin rotors for Eppendorf tubes and PCR strips as you would expect from any microcentrifuge. But that's not all. In a compact size, Centrifuge 5430 and 5430 R also accommodate rotors for microplates and 15/50 mL conical tubes. Now, the rotor program has been expanded with additional Eppendorf QuickLock® rotors. This includes 48-place rotors (1.5/2.0 mL), a 16-place rotor for Eppendorf Tubes® 5.0 mL and a swing-bucket rotor (24 × 1.5/2.0 mL). With their unmatched versatility, Centrifuge 5430 and Centrifuge 5430 R are the flagship products among the Eppendorf microcentrifuge portfolio.

Max. RCF	30,130 × g
Max. capacity	48 × 1.5/2.0 mL, 6 × 50 mL, 2 × MTP
Rotors available	12
Acceleration time ¹	14 s
Deceleration time ¹	15 s
Display	large, brightly lit LCD
Timer	30 s to 99:59 h, with continuous run function
SOFT brake function	yes
Noise level	< 58 dB(A) with Rotor F-45-30-11
Volume range	300 mL
Power supply	230 V, 50 – 60 Hz
Max. power consumption	475 W
Dimensions (W × D × H)	33 × 42 × 25 cm
Height (with open lid)	56 cm
Weight w/o accessories	29 kg
Cooling	non-refrigerated
Temperature control range	–