

## OV4-30 - Vacuum Oven

Order code: **9002.AAH13315K**



Cena bez DPH

4.300,00 Eur

Price with VAT

5.203,00 Eur

Parameters

Volume [l]

28

Inner dimensions (w x d x h) [mm]

302×305×302

External dimensions w×d×h [mm]

534×522×655

Quantitative unit

ks

- Wide temperature range that can be controlled up to 250°C.
- Improved temperature distribution. ( $\pm 1.5^{\circ}\text{C}$  at 100°C)
- 3-point temperature calibration, high temperature accuracy over a wide temperature range.
- Inner stainless steel and aluminum shelves provide excellent corrosion resistance and clean maintenance.
- Protects equipment from overcurrent and over temperature through safety circuits.
- When a vacuum is formed and maintained, the toughened glass is attached to the gasket, so it is kept confined for long-time repeated use.
- Save and use 3 frequently used temperatures.
- PC connection using RS-232 port and USB port.
- Excellent visibility and viewing angle due to application of 5-inch large LCD.
- Wait On/Off timer. (up to 999 hours 59 minutes)
- Toughened glass viewing window for easy internal viewing.
- Microprocessor PID method for precise temperature control.
- Automatic restart as it was operated after power recovery.
- Monitor via mobile app anytime, anywhere with LC Connected. (mobile monitoring system) (when purchased LC GreenBox)
- Microprocessor PID method for precise temperature control.
- Polycarbonate safety cover provided in case of toughened glass breakage.
- 12 events is recorded in case of door open, error, and etc.
- Over temperature limit function.
- Alarm if set temperature deviation outside of acceptable range