



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in Hradec Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: <http://www.helago-cz.cz>

GC-15K - Counting Scale

Order code: **0106.GC15K**



Cena bez DPH

1.052,00 Eur

Price with VAT

1.272,92 Eur

Parameters

Type Balances

Counting Scales

Series

GC

Approval (Verif. ČMI)

NO

Capacity (maximum)

15000 g

Minimum weighing value

2 g

Interface

RS-232C

Specifications

Comparator function, Counting function

Calibration

External

Weighing pan [mm]

310 × 210 mm

Features

- Automatic Item Search (AIS)*¹ to instantly find a desired unit weight
- Large internal memory to store data for up to 1,000 items
- WinCT-Counting (freeware) for easy management of item data
- Unit weight backup
- Memory capacity extension using a MicroSD card
- Three reverse-backlit LCD displays for count, weight, and unit weight data, and one OLED information display
- Information display also acting as a simplified guide for internal settings
- Diverse methods of unit weight setting
- Unit weight entry navigator
- Selectable power sources including mobile battery via USB cable
- Separable display unit
- RS-232C interface that supports digital connection with an A&D balance/scale
- Expanded scope of application using the AD-8561 series of Multi-Interfaces (sold separately)
- Comparator function with highly-visible LED traffic lights and buzzer
- Automatic Counting Accuracy Improvement (ACAI)
- Adjustable response characteristics
- Stabilization of approx. 1 second (typical)*²
- Universal Flexi Coms (UFC) to customize printout content and layout
- Auto power ON and OFF functions
- Password lock and key lock functions
- External input terminal

*¹ Patent pending

*² By default settings, the stabilization time is approx. 1.6 seconds.

External Input/Output

RS-232C interface

Multi-Interfaces (optional)

Options

GC-08: Extension cable (2 m)

GC-14: Bracket for AD-8561 and vable

Accessories

AD-8561-MI02: Multi-Interface incl. USB (Type micro B)

AD-8561-MI04: Multi-Interface incl. Terminal (4-pin) block

AD-8561-MI05: Multi-Interface incl. Terminal (7-pin) block

AD-8561-11: Terminal block cover*³

AX-KO1371-200: Crossover RS-232C cable (2 m)

AX-KO7215-150: USB cable for power supply (1,5 m)*⁴

*³ Provided as standard for the AD-8561-MI05 and can also be used for the AD-8561-MI04

*⁴ Provided as standard for the GC series

Model		GC-3K	GC-6K	GC-15K	GC-30K
Minimum unit weight* ⁵	Normal mode	0,1 g	0,2 g	0,4 g	1 g
	Fine mode	0,005 g	0,01 g	0,02 g	0,05 g
Capacity		3 kg	6 kg	15 kg	30 kg
Readability		0,0005 kg	0,001 kg	0,002 kg	0,005 kg

Number of samples

5, 10, 25, 50, 100, or an arbitrary number of pieces

Weighing pan

310 mm × 210 mm

*⁵ Selectable by internal setting