

HELAGO-CZ, s.r.o. Commercial Register maintained by the Regional Court in Hradec Králové Section C, File 17879 Kladská 1082 500 03 Hradec Králové 3 Company ID: 25 96 39 61, VAT: CZ 25963961 Phone: 495 220 229, 495 220 394 Fax: 495 220 154 GSM gate: 602 123 096 E-mail: info@helago-cz.cz Web: http://www.helago-cz.cz

## FP 56 - Drying and heating chambers with forced convection and program functions Order code: 2103.90100363



| Cena bez DPH<br>Price with VAT | 3.041,00 Eur<br>3.679,61 Eur |
|--------------------------------|------------------------------|
| Parameters                     |                              |
| Type of convection             | With forced air circulation  |
| Brand, Manufacturer            | Binder                       |
| Volume [l]                     | 60                           |
| Inner dimensions (w×h×d) [mm]  | 400 × 400 × 342              |
| Size                           | 56                           |
| Quantitative unit              | ks                           |
|                                |                              |

## **Benefits**

- High temperature accuracy thanks to APT.line<sup>™</sup> technology
- User-friendly controller with large display
- Computer interface: Ethernet
- Class 2 independent adjustable temperature safety device (DIN 12880) and class 3.1 independent temperature safety device (DIN 12880) with visual/acoustic alarm available for selection on the controller

## **IMPORTANT CHARACTERISTICS**

- Temperature range: +10°C above ambient temperature up to +300°C
- High temperature accuracy thanks to APT.line<sup>™</sup> technology
- Adjustable fan speed
- Controller with interval and real-time programming
- Electromechanical control of the exhaust air flap
- 2 chrome-plated racks
- Units up to 115 liters are stackable
- Class 2 independent adjustable temperature safety device (DIN 12880) and class 3.1 independent temperature safety device (DIN 12880) with visual/acoustic alarm available for selection on the controller
- Ergonomic handle design
- Computer interface: Ethernet
- Internal data logger, measured values can be read out in open format via USB