

## **FP 115 | Drying and heating chambers with forced convection and program functions**

Order code: **2103.90100364**



Cena bez DPH

3.804,00 Eur

Price with VAT

4.602,84 Eur

### Parameters

Type of convection

With forced air circulation

Brand, Manufacturer

Binder

Volume [l]

116

Inner dimensions (w×h×d) [mm]

550 × 550 × 383

Size

115

Quantitative unit

ks

## **Benefits**

- High temperature accuracy thanks to APT.line™ technology
- User-friendly controller with large display
- Computer interface: Ethernet
- Class 2 independent adjustable temperature safety device (DIN 12880) and class 3.1 independent temperature safety device (DIN 12880) with visual/acoustic alarm available for selection on the controller

## **IMPORTANT CHARACTERISTICS**

- Temperature range: +10°C above ambient temperature up to +300°C
- High temperature accuracy thanks to APT.line™ technology
- Adjustable fan speed
- Controller with interval and real-time programming
- Electromechanical control of the exhaust air flap
- 2 chrome-plated racks
- Units up to 115 liters are stackable
- Class 2 independent adjustable temperature safety device (DIN 12880) and class 3.1 independent temperature safety device (DIN 12880) with visual/acoustic alarm available for selection on the controller
- Ergonomic handle design
- Computer interface: Ethernet
- Internal data logger, measured values can be read out in open format via USB