



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in
Hradec Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: http://www.helago-cz.cz

OF4-05S - Forced Convection Oven (Solid door without window)

Order code: **9002.AAH14125K**



Cena bez DPH

1.836,00 Eur

Price with VAT

2.221,56 Eur

Parameters

Type of convection

With natural circulation

Brand, Manufacturer

Jeiotech

Volume [l]

61

Inner dimensions (w×h×d) [mm]

380 × 480 × 330

External dimensions (w×h×d) [mm]

558 × 684 × 648

Size

05

Quantitative unit

ks

Forced Convection Ovens (Standard, OF4-S)

Standard type that provides the device information intuitively (OF4-S)

- 3.5-Inch touch controller that enables intuitive control of the device.
- Wait on/Wait off timer setting allowing efficient test schedule management.

Reliable temperature control performance based on stable control mechanisms

- Wide temperature range of up to 250°C.
- Three-point temperature calibration that ensures high temperature accuracy over a wide temperature range.
- Available to set the upper and lower temperature limit, alarm activated to quick response when occurring the deviation.
- Excellent temperature distribution through the formation of optimal airflow for uniform heat transfer.
($\pm 1.9^{\circ}\text{C}$ or below at 100°C)

Convenient checking for the test progress and data

- RS-232/USB port and compatible software provided to enable easy device control and data management using PC. (option)
- Monitor and control via mobile app anytime, anywhere with LC Connected. (mobile monitoring system) (option)
- BMS communication port that helps monitor the device temperature on the building management system. (option)

Various safety features for improved user safety

- The upper vent hole releases effectively fume inside the oven when using local ventilation equipment. (OF4-03)
- Device surface not overheating even in operation at the highest temperature. (70°C or below, at 250°C)
- Top-rated overheating protection system. (registration KR 10-0397583)
- Over temperature limit function.
- Equivalent to IEC protection Class II.

Structural and functional features for improved user convenience

- Recording the 12 most recent events, such as start/stop of operation, the operating time, and error occurrence.
- Stacking Kit (option) ensuring the safe fitting of one unit to another, thus doubling the amount of work done in a given area for improved space efficiency.
- Hands-free™ door system to allow users to easily open the door while carrying samples with both hands.
($\pm 1.9^{\circ}\text{C}$ or below at 100°C)

Specification

Solid door (without window)

Chamber volume: 61 l

Temperature range: Amb. + 10~250°C

Fluctuation at 100°C: 0.3°C

Variation at 100°C: 1.9°C

Heating time to 100°C: 10 min

Recovery time at 100°C: 4 min

Control panel: 3.5inch TFT Color LCD

Communication interface: USB, RS-232 (Option)

Recently event record: 12

Interior dimensions (W x D x H): 380 x 330 x 480 mm

Exterior dimensions (W x D x H): 558 x 648 x 684 mm

Net weight: 53 kg

Quantity of shelves (Standard/max.): 2/5

Max. Load per shelf: 30 kg

Number of Air change per hour at 100 °C 2): 22