

VBFT.196.60.4-G - Safety Cabinet type 90

Order code: **8101.VBFT196604G**



Information about product price on demand

Parameters

Types of safety cabinets

Typ 90 - skládací dveře

Quantitative unit

ks

- Safe and approved storage of hazardous materials in workrooms
- 90 min. fire resistant cabinet in accordance with EN 14470-1 (Type 90)
- Door open arrest system (standard)

- Cylinder locking (suitable for masterkey systems)
- Extraction air inlet on the top
- Adjusting aids to compensate for uneven floor
- Earthing link (standard)

Manual Operating

- Smooth, air-damped door closing
- Minimal effort: one-hand door operation easy and safe
- Door closing system outside the storage compartment: increased protection of moving and safety relevant components against corrosion

Folding Doors

- Less depth while open, space saving
- 90° opening, interior of the cabinet completely visible
- Protection by vertical anti-trapping door strip

Your safety in the event of fire

- Automatic closing of the door by an integrated thermal release system (fusible link)

Drawers

- High storage capacity
- Sealed by welding, impervious to fluids
- Fully extractable, smooth running, with permanent delayed self-closing
- Load capacity per drawer: approx. 60 kg

Cabinet with width of 600 mm (VBFT196.60)

- Folding door
- Dimensions W × D × H (mm): exterior approx. 600 × 615 × 1968, interior approx. 450 × 520 × 1 740
- Weight approx. 260 kg
- Bottom collecting sump volume 22 l