

## **VBF.60.89-S - Width 890 mm, drawer**

Order code: **8101.VBF6089S**



Information about product price on demand

### Parameters

Types of safety cabinets

Typ 90 - spodní skříň

Color

Světle šedá

Interior equipment

Záchytná vana

Quantitative unit

ks

- Safe and approved storage of hazardous materials in workrooms
- 90 minutes fire resistance cabinet in accordance with EN 14470-1
- Cylinder locking (suitable for masterkey systems)
- The extraction air inlet is flush with the ceiling of the cabinet
- Earthing link (standard)

### Operation

- Minimal effort: door opening - easy and safe

### Drawer

- Remain open in every position
- Interior completely visible - easy and safe access to all containers

- Earthing wire with clamp inside the drawer for used containers (standard)
- Bottom collecting sump sealed by welding, impervious to fluids
- Useable interior height approx. 460 mm
- Load capacity per drawer (evenly distributed load): approx. 50 kg

#### **Doors**

- Remain open in every position
- Automatic closing of doors and drawers by an integrated thermal release system (fusible link)

#### **Interior equipment (sheet-steel, plastic laminated)**

- Drawer with bottom collecting sump
- Or wing doors with bottom collecting sump and perforated metal panel

#### **Cabinet with width of 890 mm**

- Type 90
- Dimensions W × D × H (mm): exterior approx. 890 × 570 × 600, interior approx. 770 × 450 × 500
- Weight: approx. 140 kg