

**LMH 07/12 - Laboratory muffle furnace
with s regulator Ht40AL**
Order code: **2104.610444**



Cena bez DPH

2.720,00 Eur

Price with VAT

3.291,20 Eur

Parameters

Volume [l]	7
Inner dimensions (w x h x d) [mm]	170 x 170 x 275
Input power [kW]	3
Quantitative unit	ks

Application

Furnaces are used in laboratories for heat-treatment testing of various samples, when the aggressive fouling, which would pelt with the spirals, can be formed.

Description of the construction of the furnace:

- frameless construction created by the hooped rustless metal plate
- portal of the door of the fireproof adapting pieces
- in the peep-hole of the door the protective blue glass
- door of the hooped rustless metal plate tank shaped
- thrust is extrapolated by the ductile springs
- muffle insulated by the sedge of the mineral grain and cased by the insulation desks
- door fulfilled by the insulation desk
- heating spiral winding-up on the muffle
- door equipped by the security limit switch
- feeder cables procurated by the uniphase bolts
- furnace equipped by the cooling fan
- controller HT40 enables controlling to standard value
- thermocouple of the type S, placed on the back side

Standard equipment of the furnace covers:

- controller HT40
- manual door opening up

Like an accessories as an extra we are bidding:

- controller INDUSTRY
- rotary table
- interface R 232/485
- exhaust fan
- software for the monitoring and the record of the temperature cycle
- protective atmosphere supply