

Safety cabinet type 30, door hinged right

Order code: **8101.F3019760GR**



Information about product price on demand

Parameters

Types of safety cabinets

Typ 30 - křídlové dveře

Quantitative unit

ks

- Safe and approved storage of hazardous materials in workrooms
- 30 min. fire resistant cabinet in accordance with EN 14470-1 (Type 30)
- Door open arrest system (optional)

- Cylinder locking
- Extraction air inlet on the top
- Earthing link (standard)

Operation

- Safe, oil damped door closing
- Door closing system outside the storing compartment: increased úrptection of moving and safety relevant components against corrosion

Wing Doors

- 90° opening, complete visible cabinet interior

Door open arrest system (optional)

- Holds door open and eases the storage and removal inside the cabinet

Your safety in the event of fire

- Door open arrest system with an integrated, thermal release system (fusible link), automatic closing of the doors

Base

- Integrated base (100 mm ground clearance)
- Cabinet can be transported easily with a pallet truck, as the base has a removable faceplate

Shelves

- Height adjustable (32 mm increments)
- Load capacity per shelf: approx. 75 kg

Bottom collecting sump

- Easy to remove

Cabinet with width of 1 200 mm (F30.197.120)

- Double wing doors
- Dimensions W × D × H (mm): exterior approx. 600 × 600 × 1970, Ainterior approx. 530 × 505 × 1650
- Weight approx. 200 kg
- Bottom collecting sump volume 27 l