

VBF.129.120-G - Safety Cabinet type 90

Order code: **8101.VBF129120G**



Information about product price on demand

Parameters

Types of safety cabinets

Color

Interior equipment

Quantitative unit

Typ 90 - křídlové dveře

Žlutá

Police

ks

- Safe and approved storage of hazardous materials in workrooms
- 90 minutes fire resistance cabinet in accordance with EN 14470-1 (Type 90)
- Cylinder locking (suitable for masterkey systems)
- The extraction air inlet is flush with the ceiling of the cabinet
- Adjusting aids to compensate for uneven floor
- Earthing link (standard)

Operation

- Smooth, air-damped door closing
- Minimal effort: door opening - easy and safe
- Door closing system outside the storage compartment: increased protection of moving and safety relevant components against corrosion

Wing doors

- 90° opening, interior of the cabinet completely visible

Door open arrest system (optional)

- Holds door open and eases the storage and removal inside the cabinet
- Door open arrest system with an ingrated, thermal release system (fusible link), automatic closing of the doors

Interior equipment

- 3 adjustable shelves with inclination and pull-out protection, adjustable in different height in 32 mm - load on one shelf (uniform distributed) approx. 75 kg
- Easily removable bottom collection sump with three-sided lip seal for safe collection of leakage
- 1 perforated metal plate incerted at the bottom of collecting sump

Cabinet with width of 1 200 mm (VBF.129.120)

- Double wing doors
- Dimensions w x d x h (mm): exterior approx. 1 200 x 615 x 1298, interior approx. 1 050 x 520 x 1 070
- Weight: approx. 270 kg
- Bottom collection sump volume 33 l