

524011USB - Power-CASSY® USB
Order code: **5210.524011USB**



Cena bez DPH

1.950,00 Eur

Price with VAT

2.359,50 Eur

Parameters

Quantitative unit

ks

Cascadable interface device for use as programmable current or voltage source (power function generator) with integrated current or voltage measurement.

- For connection to the USB port of a computer, another CASSY module or CASSY-Display
- Electrically isolated
- Microprocessor-controlled via the CASSY operating system (complete with software update functionality for quick and easy performance enhancements)
- Can be set up as a bench-top, console or demonstration unit (also suitable for CPS/TPS panel frames)
- Voltage supply 12 V AC via cannon plug

Technical Data:

- 1 programmable voltage source with simultaneous current measurement (e.g. for recording characteristic curves)
 - Resolution: 12 bit
 - Output range: ± 10 V
 - Measuring range: $\pm 0.1/\pm 0.3/\pm 1$ A
 - Error: $\pm 1\%$ plus 0.5% maximum range value
 - Sampling rate: 200,000 values/s (= 100,000 values/s voltage and current)
 - Number of measured values: nearly unlimited (depends on PC) up to 100 values/s, at higher measuring rate max. 32,000 values (= 16,000 values per input)
- 1 programmable current source with simultaneous voltage measurement (can be activated alternatively to voltage source)
 - Output range: ± 1 A
 - Measuring range: $\pm 1/\pm 3/\pm 10$ V
 - See voltage source for additional data
- 1 USB port for connection to a computer
- 1 CASSY bus for connecting additional CASSY modules
- Dimensions: 115 mm x 295 mm x 45 mm
- Weight: approx. 1 kg