



HELAGO-CZ, s.r.o.  
Commercial Register maintained by the Regional Court in Hradec  
Králové  
Section C, File 17879  
Kladská 1082  
500 03 Hradec Králové 3  
Company ID: 25 96 39 61, VAT: CZ 25963961  
Phone: 495 220 229, 495 220 394  
Fax: 495 220 154  
GSM gate: 602 123 096  
E-mail: [info@helago-cz.cz](mailto:info@helago-cz.cz)  
Web: <http://www.helago-cz.cz>

## UN 30 - Universal oven with natural circulation

Order code: **2107.UN30**



Information about product price on demand

### Parameters

Type of convection	With natural circulation
Brand, Manufacturer	Memmert
Volume [l]	32
Inner dimensions (w×h×d) [mm]	400 × 320 × 250
External dimensions (w×h×d) [mm]	585 × 704 × 434
Size	30
Quantitative unit	ks

### Standard delivery Universal Oven

The universally applicable lab oven U is Memmert's classic appliance for temperature control in science, research and material tests in industry. The technologically perfected masterpiece made of high-quality, hygienic, easy-to-clean stainless steel leaves nothing to be desired in terms of ventilation and control technology, overtemperature protection and precisely tuned heating technology.

# Properties

## Control of standard components

**Temperature** 1 Pt100 sensor DIN class A in 4-wire-circuit

**Control** COCKPIT adaptive multifunctional digital PID-microprocessor controller with high-definition TFT-colour display

**Timer** Digital backwards counter with target time setting, adjustable from 1 minute to 99 days

## Temperature

**Set temperature range** in °C min. 5°C above ambient up to +300°C

resolution of display for setpoint values 0.1°C up to 99.9°C, 0.5°C from 100°C and for actual values 0.1°C (LED)

## Control technology

**Function** SetpointWAIT the process time does not start until the set temperature is reached

**Language setting** German/English/Spanish/French

**Calibration** three freely selectable temperature values

**Adjustable parameters** temperature (Celsius or Fahrenheit), air flap position, programme time, time zones, summertime/wintertime

## Ventilation

**natural convection**

**Fresh air admixture** adjustment of pre-heated fresh air admixture by air flap control in 10 % steps

**Vent** vent connection with restrictor flap

## Communication

**Documentation** programme stored in case of power failure

**Programming** AtmoCONTROL software for reading out, managing and organising the data logger via Ethernet interface (temporary trial version can be downloaded). USB stick with AtmoCONTROL software available as accessory (on demand).

## Safety

**Temperature control** adjustable electronic overtemperature monitor and mechanical temperature limiter TB, protection class 1 according to DIN 12880 to switch off the heating approx. 20°C above nominal temperature

**Autodiagnostic system** for fault analysis

## Standard equipment

**Scope of delivery** incl. works calibration certificate for +160°C

**Door** fully insulated stainless steel door with 2-point locking (compression door lock)

**Housing** rear zinc-plated steel

**Interior** easy-to-clean interior, made of stainless steel, reinforced by deep drawn ribbing with integrated and protected large-area heating on four sides

**Internals** 1 stainless steel grid

## Stainless steel interior

**Max. loading of chamber:** 60 kg

**Dimensions (W x H x D) [mm]** w(A) x h(B) x d(C): 400 x 320 x 250 mm

**Volume** 32 l

## Textured stainless steel casing

w(D) x h(E) x d(F): 585 x 704 x 434 mm

## Electrical data

**Voltage Electrical load** 230 V, 50/60 Hz approx. 1600 W

## Packing/shipping data

**the appliances must be transported upright**

**Dimensions approx incl. carton** B x H x T: 660 x 890 x 650 mm

**Net weight approx.** 45 kg

**Gross weight carton approx. 61 kg**