



HELAGO-CZ, s.r.o.
Commercial Register maintained by the Regional Court in Hradec Králové
Section C, File 17879
Kladská 1082
500 03 Hradec Králové 3
Company ID: 25 96 39 61, VAT: CZ 25963961
Phone: 495 220 229, 495 220 394
Fax: 495 220 154
GSM gate: 602 123 096
E-mail: info@helago-cz.cz
Web: <http://www.helago-cz.cz>

DV2TRV - Rotate viscometer

Order code: **0204.DV2TRV**



Information about product price on demand

Parameters

Number of spindles

6

Range [mPa.s]

100 **) až 40 000 000

Series

Brookfield DV2T

Quantitative unit

ks

- 5"Full Color Touch Screen Display

- Continuously senses and displays temperature (C or F), Viscosity, % Scale, Shear Rate, Shear Stress, Speed, % Torque, and Spindle, making the instrument flexible in a variety of applications
- Accuracy $\pm 1.0\%$ of range, Repeatability $\pm 0.2\%$
- Built-in RTD Temperature Probe
- Řada volitelných funkcí
- USB PC interface
- Included: Instrument 6 spindles (RV/HA/HB) or 4 spindles (LV), PG Flash Software, RTD Temperature Probe, Convenience Pack, Carrying Case

Optional Accessories:

- RheocalcT software

*) 1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles

**) Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.