

## **3082-00 - Rotary vane pump CRVpro 8**

Order code: **8010.3082-00**



Cena bez DPH

3.042,00 Eur

Price with VAT

3.680,82 Eur

### Parameters

Pumping rate [l/min]

122

Threshold pressure [kPa]

$2 \times 10^{-4}$

Vacuum pump

Rotary oil sealed

Ultimate Pressure [Torr]

$1.5 \times 10^{-3}$

Quantitative unit

ks

The robust vacuum pump CRVpro 8 belongs to the new high-performance two-stage rotary vane pumps generation of Welch. The pump

impresses with its long service life, absolute reliability and its low maintenance requirements.

This has been enabled thanks to 3 major innovations:

- Its low running temperature, which slows down potential corrosion processes and reduces the oil consumption
- Its large oil reservoir ensures a low chemical concentration, which contributes to the prolongation of the oil exchange intervals
- Its special inside coating increases the chemical resistance of the pump

#### **Scope of delivery:**

- Pump with motor
- 3 line cords (EU/UK/US)
- 2 liters of oil
- centering ring with dirt trap
- centering ring
- 2 clamping rings

#### **Technical Data**

- Max. pumping speed at 50 Hz in m<sup>3</sup>/h (l/min): 7.3 (122)
- Max pumping speed at 60 Hz in m<sup>3</sup>/h (l/min): 8.6 (143)
- Max. pumping speed at 60 Hz in cfm (l/min): 5.1 (143)
- Ultimate pressure in mbar (Torr) without gas ballast:  $2 \times 10^{-3}$
- Ultimate pressure in mbar (Torr) with gas ballast:  $7 \times 10^{-2}$
- Wired for: 115/230V, 50/60Hz
- Intake connection: DN 16 KF
- Exhaust connection: DN 16 KF
- Sound level (dB): 50
- Dimensions (W/D/H) in mm: 463/157/230
- Oil capacity in ml: 1000
- Operating temperature in °C: 10 - 40
- Weight kg (lbs): 22.5 (49.6)
- Ship weight in kg (lbs.): 27.5 (60.6)
- Shipping carton dimensions (W/D/H) in mm: 566/330/330