

HELAGO-CZ, s.r.o. Commercial Register maintained by the Regional Court in Hradec Králové Section C, File 17879 Kladská 1082 500 03 Hradec Králové 3 Company ID: 25 96 39 61, VAT: CZ 25963961

Company ID: 25 96 39 61, VAT: CZ 2596. Phone: 495 220 229, 495 220 394

Fax: 495 220 154 GSM gate: 602 123 096 E-mail: info@helago-cz.cz Web: http://www.helago-cz.cz B-293LD1.50 - Laboratory trinocular microscope

Order code: **0501.B293LD150** 



Cena bez DPH

Price with VAT

Parameters

Microscopes types

Serie

Number of eyepieces

1.916,00 Eur

2.318,36 Eur

Laboratory

B-290

Trinocular

Number of lenses 4

Zoom of lenses  $10 \times , 20 \times , 40 \times , 50 \times$ 

Illumination X-LED

Quantitative unit ks

- Observation mode:
- Brightfield.
- Head:
- Trinocular, 360° rotating and 30° inclined.
- Interpupillary distance 48-75mm.
- Dioptric adjustement:
- On the left eyepiece tube.
- Eyepieces:
- WF10x/20 mm, high eye-point and secured by a screw.
- Nosepiece:
- Quadruple revolving nosepiece, rotation on ball bearings.
- Objectives:
- Equipped with binocular head and following objectives:
- IOS N-PLAN 10x/0.25 (Cover/No Cover), with anti-fungus treatment
- IOS N-PLAN 20x/0.40 (Cover/No Cover), with anti-fungus treatment
- IOS N-PLAN 40x/0.65 (Cover/No Cover), with anti-fungus treatment
- IOS W-PLAN MET 50x/0.75 (No Cover), with anti-fungus treatment
- · Specimen stage:
- Double layer rackless mechanical sliding stage, 150×139 mm, 75×33 mm X-Y movement range. Vernier scale on the two axes, accuracy: 0.1 mm.
- Focusing:
- Coaxial coarse and fine focusing mechanism with limit stop to prevent the contact between objective and specimen. Adjustable tension of coarse focusing knob.
- Condenser:
- Abbe N.A. 1.25, with objective-coded iris diaphragm, focusable and centerable.
- Brightfield Illumination (Fixed Koehler type):
- X-LED3 with white 3.6 W LED (6,300 K) and light intensity control.
- Multi-plug 100-240Vac/6Vdc external power supply.
- Fluorescence Illumination:
- Extra efficiency LED, with light intensity control. Peak wavelength: 465 nm, Power: 3.6W.
- Epi Fluorescence Attachment:
- Slider with 3 positions (2 fluorescence, 1 brightfield), with 1 included filterset: Fluorescence B: EX 460-490, DM 505, EM 515LP: Acridine Yellow, Acridine Orange, Auramine, DiO, DTAF,
- FITC, GFP, YFP, etc.