

OV4-65 - Vacuum Oven

Order code: **9002.AAH13325K**



Cena bez DPH

5.360,00 Eur

Price with VAT

6.485,60 Eur

Parameters

Volume [l]

65

Inner dimensions (w x d x h) [mm]

402x405x402

External dimensions wxdxh [mm]

636×622×755

Quantitative unit

ks

- Wide temperature range that can be controlled up to 250°C.
- Improved temperature distribution. ($\pm 1.5^{\circ}\text{C}$ at 100°C)
- 3-point temperature calibration, high temperature accuracy over a wide temperature range.
- Inner stainless steel and aluminum shelves provide excellent corrosion resistance and clean maintenance.
- Protects equipment from overcurrent and over temperature through safety circuits.
- When a vacuum is formed and maintained, the toughened glass is attached to the gasket, so it is kept confined for long-time repeated use.
- Save and use 3 frequently used temperatures.
- PC connection using RS-232 port and USB port.
- Excellent visibility and viewing angle due to application of 5-inch large LCD.
- Wait On/Off timer. (up to 999 hours 59 minutes)
- Toughened glass viewing window for easy internal viewing.
- Microprocessor PID method for precise temperature control.
- Automatic restart as it was operated after power recovery.
- Monitor via mobile app anytime, anywhere with LC Connected. (mobile monitoring system) (when purchased LC GreenBox)
- Microprocessor PID method for precise temperature control.
- Polycarbonate safety cover provided in case of toughened glass breakage.
- 12 events is recorded in case of door open, error, and etc.
- Over temperature limit function.
- Alarm if set temperature deviation outside of acceptable range